

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 8271-5-13 (1990): Quartz Crystal Units Used for Frequency Control and Selection, Part 5: Series CX for Oscillators, Section 13: Quartz Crystal Unit Type CX-13 [LITD 5: Semiconductor and Other Electronic Components and Devices]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE



भारतीय मानक

आवृत्ति नियंत्रण और चयन में प्रयुक्त क्वार्ट्ज
क्रिस्टल इकाइयां—विशिष्ट

भाग 5 दोलकों के लिये सी एक्स श्रेणी

अनुभाग 13 क्वार्ट्ज क्रिस्टल इकाई टाईप सी एक्स-13

Indian Standard

QUARTZ CRYSTAL UNITS
USED FOR FREQUENCY CONTROL
AND SELECTION—SPECIFICATION

PART 5 SERIES CX FOR OSCILLATORS

Section 13 Quartz Crystal Unit Type CX-13

UDC 621.373.5

© BIS 1991

BUREAU OF INDIAN STANDARDS
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

FOREWORD

This Indian Standard (Part 5/Sec 13) was adopted by the Bureau of Indian Standards on 17 May 1990, after the draft finalized by the Piezoelectric Devices for Frequency Control and Selection Sectional Committee had been approved by the Electronics and Telecommunication Division Council.

This standard shall be read in conjunction with IS 8271 (Part 1) : 1981 'Specification for quartz crystal units used for frequency control and selection: Part 1 General requirements and tests (*first revision*)'.

This standard is based on JSS 50910 (1971) 'Detail specification for crystal unit, quartz, styles QC 36, QC 37, QC 38, QC 39, and QC 42' issued by the Directorate of Standardization, Ministry of Defence, India. The type of quartz crystal unit covered in this standard is equivalent to style QC 36 of JSS 50910 (1971).

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS 2 : 1960 'Rules for rounding off numerical values (*revised*)'. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

*Indian Standard***QUARTZ CRYSTAL UNITS
USED FOR FREQUENCY CONTROL
AND SELECTION — SPECIFICATION****PART 5 SERIES CX FOR OSCILLATORS****Section 13 Quartz Crystal Unit Type CX-13****1 SCOPE**

1.1 This standard (Part 5/Sec 15) Specifies detail requirements for the characteristics of quartz crystal unit Type CX-15 used for frequency control and selections in oscillators.

2 REFERENCES

2.1 The following Indian Standards have been referred to in this standard:

<i>IS No.</i>	<i>Title</i>
4570 (Part 6) : 1984	Specification for crystal unit holders: Part 6 Metal, solder seal, two-pin crystal unit holder Type CX
8271 (Part 1) : 1981	Specification for quartz crystal units used for frequency control and selection: Part 1 General requirements and tests (<i>first revision</i>)

3 OUTLINE AND DIMENSIONS

3.1 Holder outline shall conform to Type CX [See IS 4570 (Part 6) : 1984].

4 MARKING

4.1 See 8 of IS 8271 (Part 1) : 1981.

5 CONSTRUCTION AND WORKMANSHIP

5.1 See 7 of IS 8271 (Part 1) : 1981.

6 TEST SCHEDULE AND DETAIL REQUIREMENTS**6.1 General Condition for Test**

See 9.2 of IS 8271 (Part 1) : 1981.

6.2 Test Schedule

The sequence and grouping of type, routine and acceptance tests shall be in accordance with 9.1 of IS 8271 (Part 1) : 1981.

6.3 Detail Requirements

The detail requirements applicable to this particular type of crystal unit shall be as specified in Table 1.

Table 1 Detail Requirements of Quartz Crystal Unit Type CX-13

(Clause 6.3)

SI No.	Characteristic	Requirement
(1)	(2)	(3)
a)	Type of holder	CX (see 3)
b)	Frequency range	50 to 125 MHz
c)	Frequency tolerance:	
	i) Operating temperature range	± 2 ppm
	ii) Operable temperature range	± 3 ppm
d)	Load capacitance	Infinity
e)	Mode of oscillation	Fifth mechanical overtone
f)	Temperature range:	
	i) Operating	-40°C to $+90^{\circ}\text{C}$
	ii) Operable	55°C to -40°C and $+90^{\circ}\text{C}$ to $+105^{\circ}\text{C}$
g)	Test set	TS-683/TSM
h)	Rated drive level	2.0 ± 0.4 mW
j)	Calibration values:	
	i) Resistance	60 ohms
	ii) Resistance voltage drop	0.35 volt
k)	Capacitance shunt	7 pF, <i>Max</i>
m)	Resonance resistance:	
	i) 50 to 90 MHz	50 ohms, <i>Max</i>
	ii) 90+ to 125 MHz	60 ohms, <i>Max</i>
n)	Shock [As per 9.15 (Severity A) of IS 8271 (Part 1) : 1981]:	
	i) Frequency change permitted	± 5 ppm
	ii) Resonance resistance change permitted	± 10 percent
p)	Vibration [as per 9.16.1 (Severity A) of IS 8271 (Part 1) : 1981]:	
	i) Frequency change permitted	± 5 ppm
	ii) Resonance resistance change permitted	± 10 percent
q)	Temperature cycling:	
	i) Frequency change permitted	± 5 ppm
	ii) Resonance resistance change permitted	± 10 percent
r)	Ageing	
	Frequency change permitted	± 5 ppm

Standard Mark

The use of the Standard Mark is governed by the provisions of the *Bureau of Indian Standards Act, 1986* and the Rules and Regulations made thereunder. The Standard Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well defined system of inspection, testing and quality control which is devised and supervised by BIS and operated by the producer. Standard marked products are also continuously checked by BIS for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the Standard Mark may be granted to manufacturers or producers may be obtained from the Bureau of Indian Standards.

Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act, 1986* to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

Revision of Indian Standards

Indian Standards are reviewed periodically and revised, when necessary and amendments, if any, are issued from time to time. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition. Comments on this Indian Standard may be sent to BIS giving the following reference:

Doc : No. LTD 12 (1397)

Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110002
Telephones : 331 01 31, 331 13 75

Telegrams : Manaksanstha
(Common to all Offices)

Regional Offices:

Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg NEW DELHI 110002	{ 331 01 31 331 13 75
Eastern : 1/14 C.I.T. Scheme VII M, V.I.P. Road, Maniktola CALCUTTA 700054	37 86 62
Northern : SCO 445-446, Sector 35-C, CHANDIGARH 160036	2 18 43
Southern : C.I.T. Campus, IV Cross Road, MADRAS 600113	41 29 16
Western : Manakalaya, E9 MIDC, Marol, Andheri (East) BOMBAY 400093	6 32 92 95

Branches : AHMADABAD. BANGALORE. BHOPAL. BHUBANESHWAR.
COIMBATORE. FARIDABAD. GHAZIABAD. GUWAHATI.
HYDERABAD. JAIPUR. KANPUR. PATNA. THIRUVANANTHAPURAM.